

# FLOW-THROUGH AIR DISINFECTION



## MINI TOWER 55



Air disinfection



FAN EFFICIENCY  
87 m<sup>3</sup>/h



Odor neutralization



Elimination of Germs

### The device for air flow disinfection MINI TOWER 55

This product is characterised by attractive design, high efficiency and ease of use. The UV-C lamp module, which has been hidden behind a steel casing, cleans the air through flow circulation. This allows you to work safely close to people, without endangering your surroundings. In the air purification mode the device can work 24 hours a day.

MINI TOWER 55 can be used in households as well as public areas. The device is especially recommended for offices, shops, banks, post offices and in the gastronomy and hotel industry. Wherever there is frequent contact between a small and moderate group of people.

# TECHNICAL PARAMETERS

MINI TOWER 55	
DEVICES	<b>MT55-S/B</b> - BLACK, <b>MT55-S/W</b> - WHITE
WEIGHT	~12,7 kg
DIMENSIONS	HEIGHT 1165 mm   DIAMETER 300 mm
POWER	60 W
MATERIAL COMPOSITION	POWDER PAINTED STEEL,, QUARTZ GLASS
LAMP MODULE	1 * TUV 55 W
POWER SUPPLY	230 V
FREQUENCY	50 Hz
NOISE LEVEL	40 dB
OPERATING TEMPERATURE	10 TO 45 DEGREES C
STORAGE TEMPERATURE	-10 TO 60 DEGREES C
CONTACT WITH WATER	USE ONLY IN DRY PLACES
HUMIDITY	RELATIVE AIR HUMIDITY FROM 10% TO 50%
SAFETY	PROTECTION CASE AGAINST UV-C RADIATION
ADDITIONAL EQUIPMENT	CARBON FILTER ~120 CM2
FAN EFFICIENCY	87 m <sup>3</sup> /h
COLOUR VERSIONS	BLACK, WHITE